

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

Company: AccuStandard, Inc.  
125 Market Street  
New Haven, CT 06513

Date MSDS Printed: 9/4/2008  
Preparation Date: 9/4/2008  
Information Phone Number: 203-786-5290  
Emergency Phone Number: 203-786-5290  
Hours: Mon. to Fri. 8am-5pm

Catalog Number: **P-220S-A**

Product Name: EPN

Synonyms: N/A

Formula: N/A

Molecular Weight: N/A

**SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS**

Component(s)	( 2 )	CAS #	Appr. %	ACGIH-TLV (mg/m3)		OSHA-PEL (mg/m3)	
				TWA	STEL skin	TWA	STEL skin
EPN		2104-64-5	0.01	0.1	x	0.5	x
Acetone		67-64-1	99.99	1188	1782	2400	

**SECTION 3 - HAZARDS IDENTIFICATION****Health and Environmental Hazards/Symptoms of Exposure:**

High concentrations or prolonged exposure causes headache, dizziness, nausea, irritation of eyes and respiratory tract, narcosis and eventually unconsciousness.

May cause kidney and liver damage.

Animal studies show adverse effects on fertility when females were exposed chronically to acetone during pregnancy.

**Potential Health Effects:**

Irritating to eyes.

Causes skin redness and irritation. Repeated or prolonged exposure may cause dermatitis.

May be harmful if absorbed through the skin.

May be irritating to mucous membrane and upper respiratory system.

May be harmful if inhaled.

May be harmful if swallowed.

**Routes of Entry:**

Inhalation, ingestion or skin contact.

**Carcinogenicity:**

This product is or contains a component that is classified (ACGIH, IARC, NTP, OSHA) as probably not a cancer hazard.

**SECTION 4 - FIRST AID MEASURES**

---

**Emergency First Aid:**

Get medical assistance for all cases of overexposure.

Skin contact: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

Eye contact: Immediately flush with plenty of water. After initial flushing, remove and contact lenses and continue flushing for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: Drink water and induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

---

**Flammable Properties:**

Flash Point: 1 °F (-17 °C) (cc)

Flammable Limits LEL (%): 2

Flammable Limits UEL (%): 13

Autoignition Temperature: 465 °C

Dangerous fire and explosive hazard.

HMIS® III



NFPA



Vapors can travel to a source of ignition and flash back.

Containers can build up pressure if exposed to heat.

**Extinguishing Media:**

Use alcohol foam, carbon dioxide, dry chemical, or water spray when fighting fires involving this material.

**Fire Fighting Procedures:**

As in any fire, wear self-contained breathing apparatus pressure demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

---

**Spill Response:**

Wear suitable protective equipment listed under Exposure Controls / Personal Protection. Eliminate any ignition sources until the area is determined to be free from explosion or fire hazards. Contain the release and eliminate its source, if this can be done without risk. Dispose as hazardous waste. Comply with Federal, State and local regulations.

**SECTION 7 - HANDLING AND STORAGE**

---

Store in a tightly closed container.

Store in a cool area away from ignition sources and oxidizers.

Do not breathe vapor.

Use with adequate ventilation.

Do not get in eyes, on skin or clothing.

Avoid prolonged or repeated exposure.

This product should only be used by persons trained in the safe handling of hazardous chemicals.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

**Engineering Controls and Personal Protection Equipment (PPE):**

Respiratory Protection: If workplace exposure limit(s) of product or any component is exceeded (see TLV/PEL), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your safety equipment supplier). Engineering and/or administrative controls should be implemented to reduce exposure.

Material should be handled or transferred in an approved fume hood or with adequate ventilation.

Protective gloves must be worn to prevent skin contact.

(Butyl, chloroprene, natural rubber or equivalent)

Safety glasses with side shields must be worn at all times.

**General Hygiene Considerations:**

Wash thoroughly after handling. Do not take internally. Eye wash and safety equipment should be readily available.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

---

Appearance: Clear liquid

Odor: Pungent odor

pH: N/A

Vapor Pressure: 184 mmHg (20 °C)

Vapor Density (Air = 1): 2.0 g/L

Boiling Point: 56.2 °C

Melting Point: -95.3 °C

Solubility in Water (%): Very soluble

Specific Gravity (H<sub>2</sub>O = 1): 0.789 g/cm<sup>3</sup>

Flash Point: 1 °F (-17 °C) (cc)

Explosion Limits (%): 2 to 13

Autoignition Temperature: 465 °C

Percent Volatile: 99+

Evaporation Rate (BuAc = 1): 7.7

Molecular Weight: N/A

Molecular Formula: N/A

**SECTION 10 - STABILITY AND REACTIVITY**

---

Stability: Stable

Conditions To Avoid: Heat; Contact with ignition sources

Materials To Avoid: Oxidizers  
Bases

Hazardous Decomposition: Carbon oxides  
Hazardous Polymerization: Will not occur

---

**SECTION 11 - TOXICOLOGICAL INFORMATION**

See section 3 for specific toxicological information for the ingredients of this product.

---

**SECTION 12 - ECOLOGICAL INFORMATION**

By complying with sections 6 and 7 there will be no release to the environment.

---

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Recycle or incinerate at any EPA approved facility or dispose in compliance with Federal, State and local regulations. Empty containers must be triple-rinsed prior to disposal.

---

**SECTION 14 - TRANSPORT INFORMATION**

DOT   UN Number:   UN1090   Shipping Class: 3   Packing Group: II   FLAMMABLE

---

**SECTION 15 - REGULATORY INFORMATION**

In addition to Federal and state regulations, local regulations may apply. Check with your local regulatory authorities.

Not all components are listed on the TSCA Inventory. For laboratory, reasearch and development use only. Not for manufacturing or commercial purposes.

---

**SECTION 16 - OTHER INFORMATION**

This document has been designed to meet the requirements of OSHA, ANSI and CHIPs regulations.

The statements contained herein are offered for informational purposes only and are based on technical data that we believe to be accurate. It is intended for use only by persons having the necessary technical skill and at their own discretion and risk. Since conditions and manner of use are outside our control, we make  
NO WARRANTY, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE.

Legend : N/A = Not Available   ND = Not Determined   NR = Not Regulated  
\* \* \* End of Document \* \* \*