

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Company: AccuStandard, Inc.
 125 Market Street
 New Haven, CT 06513

Date MSDS Printed: 9/14/2007
 Preparation Date: 9/14/2007
 Information Phone Number: 203-786-5290
 Emergency Phone Number: 203-786-5290
 Hours: Mon. to Fri. 8am-5pm EDT

Catalog Number: APP-9-149-M-10X
 Product Name: N-Nitrosodimethylamine
 Synonyms: N/A
 Formula: N/A

Molecular Weight: N/A

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

Component(s) (1)	CAS #	Appr. %	ACGIH-TLV (mg/m3)		OSHA-PEL (mg/m3)	
			TWA	STEL skin	TWA	STEL skin
N-Nitrosodimethylamine	62-75-9	0.10				
Methanol	67-56-1	99.90	262	328 x	260	

SECTION 3 - HAZARDS IDENTIFICATION

Health and Environmental Hazards/Symptoms of Exposure:

Over exposure may cause dizziness, nausea, muscle weakness, narcosis and respiratory failure. After ingestion or inhalation, initial symptoms may be only that of mild intoxication, but may become severe after 12 or 18 hours. May cause eye, kidney, liver, and skin damage. May cause central nervous system damage. POISON: May be fatal or cause blindness if swallowed. Fetal development abnormalities and effects on embryo or fetus have been reported from prolonged exposure to methanol in laboratory tests involving pregnant rats.

HMIS® III * 2 3 0

NFPA 2 3 0

Potential Health Effects:

- Irritating to eyes.
- Irritating to skin.
- Toxic if absorbed through skin.
- Irritating to mucous membrane and upper respiratory system.
- Toxic if inhaled or swallowed.

Routes of Entry:

Inhalation, ingestion or skin contact.

Carcinogenicity:

This product is or contains a component that is classified (ACGIH, IARC, NTP, OSHA) as a suspect cancer hazard.

SECTION 4 - FIRST AID MEASURES

Emergency First Aid:

- Get medical assistance for all cases of overexposure.
- Skin contact: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.
- Eye contact: Immediately flush with plenty of water. After initial flushing, remove and contact lenses and continue flushing for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers.
- Inhalation: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

M A T E R I A L S A F E T Y D A T A S H E E T

Ingestion: Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties:

Flash Point: 52 °F (11 °C) (tcc)

Flammable Limits LEL (%): 6.7

Flammable Limits UEL (%): 36.5

Autoignition Temperature: 385 °C

Dangerous fire and explosive hazard.

Containers can build up pressure if exposed to heat.

Vapors can travel to a source of ignition and flash back.

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Extinguishing Media:

Use alcohol foam, carbon dioxide, dry chemical, or water spray when fighting fires involving this material.

Fire Fighting Procedures:

As in any fire, wear self-contained breathing apparatus pressure demand, MSHA/NIOSH (approved or equivalent) and full protective

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Spill Response:

Wear suitable protective equipment listed under Exposure Controls / Personal Protection. Eliminate any ignition sources until the area is determined to be free from explosion or fire hazards. Contain the release and eliminate its source, if this can be done without risk. Dispose as hazardous waste. Comply with Federal, State and local regulations.

SECTION 7 - HANDLING AND STORAGE

Store in a tightly closed container.

Store in a cool area away from ignition sources and oxidizers.

Avoid breathing vapors or mists.

Use with adequate ventilation.

Do not get in eyes, on skin or clothing.

Avoid prolonged or repeated exposure.

This product should only be used by persons trained in the safe handling of hazardous chemicals.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls and Personal Protection Equipment (PPE):

Respiratory Protection: If workplace exposure limit(s) of product or any component is exceeded (see TLV/PEL), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your safety equipment supplier). Engineering and/or administrative controls should be implemented to reduce exposure.

Material should be handled or transferred in an approved fume hood or with adequate ventilation.

(Chloroprene, natural rubber, nitrile, or equivalent)

Safety glasses with side shields must be worn at all times.

Safety glasses with side shields must be worn at all times.

General Hygiene Considerations:

Wash thoroughly after handling. Do not take internally. Eye wash and safety equipment should be readily available.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear liquid

Odor: N/A

pH: N/A

Vapor Pressure: 97 mmHg (20 °C)

M A T E R I A L S A F E T Y D A T A S H E E T

Vapor Density (Air = 1): 1.1 g/L
Boiling Point: 65 °C
Melting Point: -93.9 °C
Solubility in Water (%): Very soluble
Specific Gravity (H₂O = 1): 0.791 g/cm³
Flash Point: 52 °F (11 °C) (tcc)
Explosion Limits (%): 6.7 to 36.5
Autoignition Temperature: 385 °C
Percent Volatile: 99.9+
Evaporation Rate (BuAc = 1): 5.9
Molecular Weight: N/A
Molecular Formula: N/A

SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable

Conditions To Avoid: Heat; Contact with ignition sources

Materials To Avoid: Acids
Oxidizers
Alkali metals; Reducing agents

Hazardous Decomposition: Carbon oxides; Formaldehyde

Hazardous Polymerization: Will not occur

SECTION 11 - TOXICOLOGICAL INFORMATION

See section 3 for specific toxicological information for the ingredients of this product.

SECTION 12 - ECOLOGICAL INFORMATION

By complying with sections 6 and 7 there will be no release to the environment.

SECTION 13 - DISPOSAL CONSIDERATIONS

Recycle or incinerate at any EPA approved facility or dispose in compliance with Federal, State and local regulations. Empty containers must be triple-rinsed prior to disposal.

SECTION 14 - TRANSPORT INFORMATION

DOT UN Number: UN1230 Shipping Class: 3 Packing Group: II **FLAMMABLE**

SECTION 15 - REGULATORY INFORMATION

In addition to Federal and state regulations, local regulations may apply. Check with your local regulatory authorities.

All components are listed on the TSCA Inventory.

WARNING: This product contains chemical(s) known to the state of California to cause cancer.

SECTION 16 - OTHER INFORMATION

This document has been designed to meet the requirements of OSHA, ANSI and CHIPs regulations.

M A T E R I A L S A F E T Y D A T A S H E E T

The statements contained herein are offered for informational purposes only and are based on technical data that we believe to be accurate. It is intended for use only by persons having the necessary technical skill and at their own discretion and risk. Since conditions and manner of use are outside our control, we make
NO WARRANTY, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE.

Legend : N/A = Not Available ND = Not Determined NR = Not Regulated

* * * End of Document * * *